

FAA STYLE A OBSTRUCTION LIGHTING



INCLUSIONS / SPECIFICATIONS

BEACON

Lamp type	LED, Red - Night L-864
Effective intensity	2,000 cd - Night
Horizontal coverage	360°
Vertical beam	3°
Power consumption	6.8 - 30 watts Night
Weight	15 lbs, Power Supply 7 lbs, Flash Head
Dimensions	PS, 12.19" x 14" x 6.68" FH, 6.7" dia. x 5"
Operating temperature	-40°F to 131°F (-40°C to 55°C)
Power requirements	120/240 V AC, 50/60hz Also available in 24V DC
Warranty	5 years (Refer to full warranty statement)

FAA - STYLE - A

LED

FEATURES

- Two-conductor wire with polarity protection
- One size cable for Beacon, Markers, Photocell
- High power LEDs driven at low current levels for MAX life
- Standard 13 1/4" bolt circle
- Controller and power supply are located at ground level
- Includes FAA required monitoring (dry contacts)
- SNMP network alarm (available)
- ADLS - aircraft detection lighting system interface

DAY **NIGHT**

SIDE MARKER

Lamp type	LED, Red - Night L-810 (F)
Effective intensity	32cd - Night
Warranty	5 years (Refer to full warranty statement)

L-SHAPE BRACKET

Metal type	Aluminum
Hose Clamps	All stainless steel

CABLE

Type	UV resistant, UL, 2C, 16 AWG
------	------------------------------

CERTIFIED

Intertek	FAAAC 150/5345-43G RED-LED-Standard
----------	--